

C-120

Dual radio, dual concurrent 4x4:4 MU-MIMO 802.11ac Wave 2 access point

Key Specifications

- Up to 800 Mbps for 2.4GHz radio
- Up to 1.7 Gbps for 5GHz radio
- 802.11ac Wave 2 support
- 4x4 MU-MIMO with four spatial streams per radio
- Eight integrated omnidirectional antennas
- 20/40/80/80+80/160 MHz channel width support
- 2x Gigabit Ethernet port
- Full operational capacity with 802.3at PoE
- Wall and ceiling mounting support



Ergonomic Design and High Performance

The Mojo C-120 is an enterprise-grade 4x4 MU-MIMO 802.11ac access point with dual concurrent 5 GHz and 2.4 GHz band radios supporting 802.11a/n/ac Wave 2, 802.11b/g/n, four spatial streams, and data rates of up to 1.7 Gbps and 800 Mbps, respectively.

Why Choose the C-120?

The C-120 is a leader in the next generation 802.11ac access point ecosystem, boasting four antennas and four spatial streams for truly unprecedented throughput and client capacity capabilities. The C-120 is a must for all critical, high-density networks that expect a high volume of diverse clients with diverse needs. Common deployment scenarios include large schools, large remote offices, auditoriums, meeting rooms, and enterprise campuses.

With its Wave 2 chipset, the C-120 takes advantage of the latest modulation and beamforming techniques to transform WiFi networks and offer the speeds and reliability once thought only possible over the wire. Best of all, the C-120 offers this best-in-class performance at a similar cost of competitive 802.11ac Wave 1 access points.

Mojo Cloud Managed WiFi

The C-120 is managed by the Mojo cloud managed platform which enables a complete workflow for wireless access, security and engagement. It leverages a purpose-built cloud architecture to produce enterprise-grade wireless

Key Features

- 100% controller-free
- Zero-touch deployment through automatic cloud activation and configuration
- Cloud-defined operating modes for dedicated access, dedicated security or dual-mode
- Support for up to eight distinct SSIDs per radio
- Integrated firewall, traffic shaping, QoS and BYOD controls per SSID
- Dynamic RF optimization through smart steering, band steering and optimal channel selection
- Automated device access logging
- No-WiFi VLAN monitoring for extended rogue access point detection
- Third party analytics integration for real-time data transfer
- Self-healing wireless mesh networking

networks for every application required, and ensures high reliability through an approach that is automated, scalable, secure and cost effective.

What really matters

The future of WiFi requires intelligent, self-reliant access points that support high-performing, highly reliable networks without the need of antiquated controllers. This approach removes the complexity, instability and high costs associated to enterprise WiFi today.

Access

The C-120 creates WiFi networks that require less time and resources to deploy and maintain compared to traditional devices, resulting in significant cost savings.

- Mojo access points take less than two minutes to activate and configure after connecting to the cloud
- Support for up to eight individual SSID's per radio allows for maximum flexibility in network design
- Network controls like NAT, Firewall and QoS occur at the access point level, ensuring faster and more reliable networks
- Persistent scanning of all 802.11 channels results in increased insight and data about surrounding environmental factors that assist in RF optimization and client handling
- Smart steering addresses sticky client issues by automatically pushing clients with low speeds to a closer access point
- Band steering manages channel occupancy, pushing clients to the 5GHz channel for optimal throughput
- Access points continue to broadcast and support wireless networks even if their connection with the cloud is interrupted

Security

The C-120 offers complete visibility and control of the wireless airspace that keeps the integrity of the network in check and actively protects users without manual intervention.

- Every Mojo access point is equipped with the industry's only fully integrated wireless intrusion prevention capabilities
- Runs complete spectrum scans while simultaneously serving wireless clients without a third radio
- Mojo's patented Marker Packets™ are used to accurately detect access points on any network with the fewest false positives in the industry
- Mojo access points can be converted to a dedicated security sensor with a single click for maximum wireless protection
- VLAN monitoring enables a virtual connection to non-WiFi networks for complete network rogue detection and prevention
- Automatic prevention combines over-the-wire and over-the-air techniques to keep unauthorized clients on the network and authorized clients on it
- Access points continue to scan for wireless threats and enforce security policy even if their connection with the cloud is interrupted

Engagement

The C-120 collects massive amounts of data and supports immersive guest network experiences that develops and reinforces the relationship between them and the brand.

- Persistent scanning of all 802.11 channels results in a comprehensive list of active wireless clients across the enterprise
- Choice statistics like location, duration, distance from access point and time of day are stored locally for every active wireless client
- Choice statistics like session duration, total data transfer up and down, data rate, smart device type and top-level domain are stored locally for every active connection
- Real-time notifications sent to third party systems that alert to the presence of enrolled devices
- Enables proximity marketing programs that trigger when certain devices are present
- Triggers automatic messaging via MMS, in-browser notifications and more

About Mojo Networks, Inc.

Mojo Networks is redefining the modern WiFi platform. Imagine the scalability to set up millions of access points with a few clicks, all from your smartphone. Envision an Internet experience that engages users with your business to drive results. Stay secure on the same WiFi cloud powering major brands and the highest levels of government. And enjoy the cost savings of a cloud-first solution without the pricey markup of proprietary hardware. Welcome to the era of prolific connectivity. Founded in 2003, Mojo Networks (formerly known as Mojo Networks), serves customers in the Fortune 500, Global 2000 and large carriers around the world. Request a free demo of Mojo Cloud Managed WiFi Platform at www.mojonetworks.com

Technical Specifications

Physical Specifications	
Dimensions	1220mm X 220mm X 40mm
Antenna	Internal PIFA x8 (x4 per band band)
Ethernet Ports	2 Gigabit Ethernet ports with RJ45 connector type. One port to connect to the wired LAN and communicate with the Mojo Cloud or Server. This port can also be used to power the device using the 802.3af Power over Ethernet (PoE) standard. Second port can be used for aggregation or wired extension of an SSID
USB	1 USB 2.0 port
LEDs	Ethernet, 2.4Ghz, 5GHz
Operational Specifications	
Input Power	12V DC (6.3mm connector)/802.3af (PoE)/802.3at (PoE+)
Operating Temperature	32°F – 104°F (0°C – 40°C)
Storage Temperature	-13°F – 167°F (-25°C – 75°C)
Humidity	0-95% non-condensing
Number of Radios	2 concurrent; 2.4GHz and 5GHz
MIM	4 X 4
Number of Spatial Streams	4
RF Transmit Power	24dBm per radio (max); Actual power for Tx will depend on Country Regulatory Domain
80 MHz + 80 MHz Non Contiguous Channel Bonding	Yes
Simultaneous MU-MIMO Clients	64
Users in a MU-MIMO group with a 2x2 client	3
Bandwidth Agility	Yes
Small Cells Interference Mitigation (picocells, femtocells, microcells)	Supported
Frequency Bands	2.4-2.4835 GHz, 4.9-5.0GHz, 5.15-5.25 GHz (UNII-1), 5.25-5.35 GHz, 5.47-5.6 GHz, 5.650-5.725 GHz (UNII-2), 5.725-5.85 GHz (UNII-3)
Dynamic Frequency Selection	Supported in compliance to all latest amendments from FCC, CE, IC, CB, TELEC, KCC regarding certifications.

